

Quotation Request //

US Government Printing Office

Agency Publishing Services
732 North Capitol Street, NW
Washington DC 20401-0001

JACKET:326-565

Issue Date and Time: 09/25/2006 5:40 PM

Quotations are Due By:

(Eastern Time)10:00 AM on 09/26/2006

Submit Fax Quotes to: 00000000

TITLE: FT 105-ADD-F-1

QUANTITY: 70 books

TRIM SIZE: 5-7/8 x 9-1/8"

PAGES: 96 plus separate wraparound cover.

SCHEDULE:

Furnished Material will be available for pickup by 09/26/2006

Ship complete by 10/24/2006

F.O.B. destination

FURNISHED STOCK WILL BE MADE AVAILABLE FOR PICKUP BY 09/28/06.

QUALITY LEVEL: 3 Quality Assurance Through Attributes (GPO PUB 310.1, effective May 1979 (Rev. 8-02)) applies.

DESCRIPTION:

Print or stamp Covers 1 and 4 with blue type and rule matter, image sizes 5-7/8 x 6-7/8" for Cover 1 and 1 x 3/32" for Cover 4. Stamping/printing must have solid impression with no picking, pinholes or filling in. Stamp or print using the dies or negative as applicable. NOTE: If the cover is printed, coat the entire surface of covers 1, 4 and backstrip with a clear non-yellowing varnish or lacquer after printing to prevent scratching and smearing. Covers 2, 3 and backstrip plus endleaves are blank.

Text pages A, B, I-XII, 1-82 with pages 81 and 82 blank. Pages 6-11, 18-23, 28-33, 38-44, 48-55, 61-67, and 73-79 print in brown and black. The balance of text pages print in black ink only. There are no halftone or flat tone text pages. Cut-in indexing is required.

Cut-In Indexing: Cut-in a 1/4" wide lip index on the 9-1/8" outside edge. Pages 3 and 4 of the front endleaf plus text pages A, B, I and II must be trimmed 1/4" short of the outside edge (flush with cut-in index). See the chart below for positions, depth of cuts, etc. All of the indexes must be visible when cover 1 is open.

Position No. Identified as:	Page No.	No. of Leaves per cut tab (inches)	First Leaf of cut	Depth of uncut
1	III - 2	6	Introduction	1-1/4"
2	3 - 14	6	Charge 1	2-3/8"
3	15 - 24	5	Charge 2	3-1/2"
4	25 - 34	5	Charge 3	4-5/8"
5	35 - 44	5	Charge 4	5-3/4"
6	45 - 56	6	Charge 5	6-3/4"
7	57 - 68	6	Charge 6	8"
8	69 - 82	7	Charge 7	Full Depth (no cut)

Special Requirement for the Ink: INKS must be permanent, durable, and water-resistant. The contractor must maintain the ink density on Pantone's 174 to plus/minus .03 from 1.10 on the densitometer yellow channel throughout the press run. Color bars on the press sheets are recommended for use in checking of the density. The ink density is critical due to the fact that this publication will be used in infrared lighting environments.

MATERIAL FURNISHED: Contractor to pickup at GPO. One complete set of film negatives.

